

WARP Mechanics® AP-3213-JS24 Versatile Application Platform

Features & Benefits

- 24x 2.5" drive bays in a 2U chassis, 12Gbps SAS capable
- Energy Efficient Xeon E5-2600 v3 Processor
- Up to 90% increase in workload performance
- Support for up to 24 DDR4 DIMMs
- Up to 7 PCIe slots in a 2U chassis via 3 riser cards
- I/O modules available with 1/10/40GbE or FDR InfiniBand* (does not consume PCIe* card slots)

The power and performance of the Intel® Xeon® processor E5-2600 v3 family reaches peak efficiency with the **WARP Mechanics AP-3213-JS24**, a rack mount Application Platform delivering world-class performance in a package optimized for CPU and RAM density, a full range of PCIe slot options, and a highly-capable internal switched SAS architecture. This workhorse platform is the basis for several WARP Mechanics turnkey storage server appliances.

High memory capacity, networking, storage and I/O flexibility combine with innovative design to provide an exceptional and reliable server for business IT, appliance, data center, cloud and high performance computing applications. The AP-3213-JS24 components are sourced through authorized suppliers to show the transparency and traceability of its supply chain with the Intel® Transparent Supply Chain. This traceability establishes accountability of manufacturing and helps to fight the infiltration of counterfeit components.

The AP-3213-JS24 may contain up to two 18-core processors, yielding 36 cores and 1.5TB of RAM per chassis. In addition to the onboard 1Gb/10GbE ports, the platform contains a wide range of high-speed I/O interfaces. Multiple embedded I/O modules are available with 1/10/40GbE or FDR InfiniBand, freeing up its PCIe slots for other purposes such as additional 1/10/40Gbps Ethernet, 6/12Gbps SAS, or 40/56/100Gbps InfiniBand for extremely dense IO connections.


The AP-3213-JS24 provides an Integrated Management Module for IPMI 2.0 management with virtual KVM and comes with 24x hot-swap 3.5" drive bays in front via a SES-compliant 12Gb SAS expander, and an optional 2x 2.5" hot-swap drive bays in the rear. For larger capacity, combine it with any of the WARP Mechanics storage platforms or appliances such as the ultra-dense WDS-9460 JBODs, which scales to over nine petabytes connected to any given AP-3200.



Wherever you and your company need to go, the WARP Mechanics portfolio can get you there, faster and more cost-efficiently than any other products in their class.

WARP Mechanics® AP-3213-JS24

Technical Specifications



Ordering Part Number and Product Name

VDC-032103-JS24 • AP-3213-JS24 Application Platform

Server Board Specification

CPU:

- Dual Intel® Xeon® E5-2600 v3, up to 145W TDP, Socket-R3 LGA2011-3

Memory Spec:

- Up to 1.5TB using 64GB DIMMs, DDR4 RDIMMs/LRDIMMs max 2133MT/s
- 24 DIMMs, 3 DIMMs per channel, 4 channels per processor
- DDR4 Speed: 1600MT/s, 1866MT/s, 2133
- Voltage: 1.2V, DDR4 Standard I/O voltage

PCIe Architecture

Ethernet:

- Dual RJ45, Network Connectors supporting 10GBaseT & 1GBaseT
- Single RJ45, Dedicated 1GbE server management port

I/O Modules:

- One proprietary multi-port IO Module (10Gb SFP+/40Gb QSFP/FDR QSFP)
- One proprietary internal (x8 PCIe) supporting Intel® RAID Module

Riser Card 1 (2x PCIe 3.0):

- one x16 Electrical, x16 (Mech), one x8 Electrical, x8 (Mech)

Riser Card 2 (2x PCIe 3.0):

- two x8 Electrical, x16 (Mech), one x8 Electrical, x8 (Mech)

Riser Card 3 (1x PCIe 2.0, 1x PCIe 3.0):

- one x4 Electrical, x8 (Mech), one x8 Electrical, x8 (Mech)
- Note: the x4 slot may hold the Intel RES3FV288 12Gb SAS expander

Redundant Hot-Swap Components

- 24 SATA/SAS 2.5" drive modules
- Two rear-mounted 2.5" SATA drives
- Two 1100W power supplies (PSU)

Rackmount Enclosure

Chassis Dimensions:

- 17.25" (438.15mm) W x 28" (711.20mm) L x 3.44" (87.38) H

Packaging Dimensions:

- 22.72" (577mm) W x 38.70" (983mm) L x 10.23" (260mm) H

PSUs per chassis:

- Up to 2, supporting 1+0, 1+1 Redundant Power and 2+0 Combined Power

Power Supply:

- 1100W AC 80 PLUS Platinum (optional 750W AC & 750W DC available)

Fans:

- Six managed Hot-swap system fans

Disk Drive Modules

Twenty-four (24) 2.5" front bays:

- Up to 8x 6Gbps SATA drives -or-
- Up to 24x 12Gbps SAS drives with SAS controller and expander

Two (2) 2.5" rear bays:

- Optional 2.5" Rear mount 6Gbps SATA Hot-swap drives

Server Management

BMC Management:

- Integrated Baseboard Management Controller, IPMI 2.0 compliant
- Dedicated RJ45 management port
- Remote KVM Management and device mapping via Intel® RMM4-Lite accessory

BIOS Type: UEFI BIOS

Intel® Transparent Supply Chain:

- Includes Statement of Conformance and Platform Certificate
- TPM Version 1.2

Firmware/Software

WARP Mechanics controller firmware supports SES 3.0 for in-band and IPMI 2.0 for out-of-band management. WARPware hosts include tools for managing firmware and advanced features.

Monitoring and Reporting

Monitoring for temperature, advanced power and cooling modules including blower speed control, disk drives and I/O module(s). In-band reporting of all serial number, part number and revisions of each FRU and chassis via IPMI/SES.

Warranty Information

Standard one year; up to three via normal renewable support; extended to five years in special circumstances for large installations. Contact WARP Mechanics sales to discuss special requirements.

Power

Voltage: 90 Hz to 132 V and 180 V to 264 V

Frequency: 47 Hz to 63 Hz

Source Interrupt: No loss of data for power line drop-out of 12 mSec

Surge Non-operating and operating: Unidirectional

Line to earth only:

- AC Leads 2.0 kV
- I/O Leads 1.0 kV
- DC Leads 0.5 kV

Operating Environment

Temperature: +10°C to +35°C, max. change rate <10°C per hour.

Acoustic noise, Sound power: 7.0BA with HDD stress at ambient (23 +/-2°C)

Shock: Half sine, 2g peak, 11 mSec

ESD: +/-12 KV except I/O port +/- 8 KV

System Cooling: 1600 Watt Max – 5459 BTU/hour

Non-Operating Environment

Temperature: -40°C to +70°C

Relative humidity: 90%, non-condensing at 35°C

Vibration: 5 Hz to 500 Hz, 2.20 g RMS random

Shock: 25g, velocity change 205 inches/second (80 lbs. to < 100 lbs.)

Standards Compliance

IEC/EN/UL/CSA 60950-1, 2nd Edition

RoHS and WEEE compliant

EN55022 :2006 + A1 :2007

EN55024-IT product family standard for Immunity

Meet the requirements of IEC62301

Manufactured under an ISO 9002 registered quality system

Copyright © 2016 WARP Mechanics Ltd. All Rights Reserved

WARP Mechanics, WARPware, the WARP Mechanics logo, the WARP Mechanics icon, and SmartStorage System are trademarks of WARP Mechanics Ltd. in the United States and other countries. Other brand, product, or service names may be trademarks or service marks of, and are used to identify, products or services of their respective owners. This document is supplied "AS IS" for information only, without warranty of any kind, expressed or implied. WARP Mechanics reserves the right to change this document at any time, without notice.